













Optoma Projector Range (it)



	0	Ultra Mobile LED		
				
	DX346	ML750e	ML750ST	ML1500e
Risoluzione	Nativa XGA 1024 x 768	Nativa WXGA 1280 x 800	WVGA 854 x 480	Nativa WXGA 1280 x 800
Luminosità ¹ (Modalità luminosa)	3000 ANSI Lumen	700 LED Brightness*	800 Luminosità LED*	1500 LED Brightness*
Contrasto	18,000:1	15,000:1	20,000:1	20,000:1
Livello Rumore Audio (Modalità ECO)	29dB	30dB	22dB	30dB
Peso (Kg)	2.35	0.38	0.42	1.4
Durata Lampada ² (hrs)	6500/6000/5000 Dynamic/Eco/Bright	20,000 (LED Life) Bright	20,000 (LED) Bright	20,000 hours LED Life Bright
Dimensioni (WxDxHmm)	314.6 x 222.6 x 101.7	105 x 106 x 39	112.5 x 123 x 57	270 x 170 x 42
Dimensione Immagine		0.43 - 2.54m (17" - 100") Diagonal 16:10	0.43 - 2.54m (17" - 100") Diagonal 16:10	0.43 - 2.54m (17" - 100") Diagonal 16:10
Rapporto di Proiezione	1.95 - 2.15:1	1.5:1	0.8:1	1.4:1
Tipo Di Zoom	1.1x Manuale	-	-	-
Correzione Trapezio	± 40° Verticale	±40° Vertical	±40° Verticale (Auto)	±40° Vertical (Auto)
Connessioni		HDMI + MHL v1.0, Universal I/O - VGA / Audio Out 3.5mm, microSD-slot, USB-A reader/wireless	HDMI + MHL v2.0, Universal I/O - VGA, microSD-slot, USB-A reader/wireless, Audio out	HDMI, VGA (YPbPr/RGB), Composite, Audio In 3.5mm, Audio Out 3.5mm, SD card slot, 2 x USB-A reader/wireless, micro USB
Wireless Opzionale	Si	Si	Si	Si
Speaker (Watts)		1	1.5	6W stereo (2x3W) SRS WOW HD Audio
Borsa	Si	Si	Si	Si
Caratteristiche	Fino a 10.000 ore della lampada - Ciclo di Istruzione	Native office viewer, media player, 1.5GB memory, LED light source, optional wireless presenting		Native office viewer, media player, LED light source, optional wireless presenting

	Ultra Portatile		Portatile	
				
	X304M	W304M	DS340e	S310e
Risoluzione	Nativa XGA 1024 x 768	Nativa WXGA 1280 x 800	Nativa SVGA 800 x 600	Nativa SVGA 800 x 600
Luminosità ¹ (Modalità luminosa)	3000 ANSI Lumen	3100 ANSI Lumen	3000 ANSI Lumens	3200 ANSI Lumens
Contrasto	10,000:1	10,000:1	18,000:1	20,000:1
Livello Rumore Audio (Modalità ECO)	33dB	33dB	29dB	29dB
Peso (Kg)	1.4	1.4	2.35	2.35
Durata Lampada ² (hrs)	4000/5000 Eco/Bright	4000/5000 Eco/Bright	5000 Bright	5000 Bright
Dimensioni (WxDxHmm)	220 x 178 x 71	220 x 178 x 71	315 x 224 x 102	315 x 224 x 102
Dimensione Immagine	0.68m - 5.26m 33.58" - 259.25" Diagonale 4:3	0.68 - 6.54m (31.65" - 303.44") Diagonale 16:10		
Rapporto di Proiezione	1.9 - 2.2:1	1.53 - 1.76:1	1.95 - 2.15:1	1.95 - 2.15:1
Tipo Di Zoom	1.15x Zoom Manuale	1.15x Manuale	1.1x Manual	1.1x Manual
Correzione Trapezio	± 30° Verticale	± 30° Verticale	± 40° Vertical	± 40° Vertical
Connessioni	HDMI (1.4a 3D support), VGA (Wireless/YPbPr/RGB), Composite, Audio In 3.5mm, Audio Out 3.5mm, USB (Remote Mouse)	HDMI (1.4a 3D support), VGA (Wireless/YPbPr/RGB), Composite, Audio In 3.5mm, Audio Out 3.5mm, USB (Remote Mouse)	VGA (YPbPr/RGB/Wireless), S-Video, Composite, RS232, USB service	VGA (YPbPr/RGB/Wireless), S-Video, Composite, RS232, USB service
Wireless Opzionale	No	No	Si	Si
Speaker (Watts)	1			
Borsa	Si	Si	Si	No
Caratteristiche	Leggero e Portatile	Il più piccolo e più brillante proiettore WXGA		

	Portatile			
				
	S321	S311	S331	DS344
Risoluzione	Nativa SVGA 800 x 600	Nativa SVGA 800 x 600	Nativa SVGA 800 x 600	Nativa SVGA 800 x 600
Luminosità ¹ (Modalità luminosa)	3200 ANSI Lumen	3200 ANSI Lumens	3200 ANSI Lumen	3000 ANSI Lumen
Contrasto	22,000:1	20,000:1	22,000:1	18,000:1
Livello Rumore Audio (Modalità ECO)	29dB	28dB	29dB	29dB
Peso (Kg)	2.17	2	2.17	2.35
Durata Lampada ² (hrs)	8000/7000/6000/5000/10000 Eco+/Dynamic/Eco/Bright/Educationcy cle	7000/6500/6000/5000 Eco+/Dynamic/Eco/Bright	8000/7000/6000/5000/10000 Eco+/Dynamic/Eco/Bright/Educationcy cle	7000/6500/6000/5000/10000 Eco+/Dynamic/Eco/Bright/Educationcy cle
Dimensioni (WxDxHmm)	298 x 230 x 96.5	287 x 193 x 113	298 x 230 x 96.5	315 x 224 x 102
Dimensione Immagine		0.69 - 7.62m (27.24" - 300.04") Diagonal 4:3		0.58 - 7.62m (22.9" - 300") Diagonal 4:3
Rapporto di Proiezione	1.94 - 2.16:1	1.97 - 2.17:1	1.94 - 2.16:1	1.95 - 2.15:1
Tipo Di Zoom	1.1x Manuale	1.1x Manual	1.1x Manuale	1.1x Manuale
Correzione Trapezio	± 40° Verticale	± 40° Vertical	± 40° Verticale	± 40° Verticale
Connessioni	VGA (YPbPr/RGB), Composite, USB mouse/service	2x HDMI (1.4a 3D support), RS232, USB remote mouse/service, USB-A Power	2x HDMI (1.4a 3D support) + MHL, Audio out 3.5mm, USB-A Power (5V-1A)	HDMI (1.4a 3D support), VGA (YPbPr/RGB), S-Video, Composite, Audio In 3.5mm, RS232, USB Service, USB-A Power (5V-1A)
Wireless Opzionale	Si	Si	Si	Si
Speaker (Watts)		2	2	2
Borsa	No	Si	No	No
Caratteristiche				

Portatile



DS335



DS346i



S312



S316

Risoluzione	Nativa SVGA 800 x 600	Nativa SVGA 800 x 600	Nativa SVGA 800 x 600	Nativa SVGA 800 x 600
Luminosità ¹ (Modalità luminosa)	3200 ANSI Lumen	3000 ANSI Lumen	3200 ANSI Lumen	3200 ANSI Lumen
Contrasto	18,000:1	18,000:1	20,000:1	20,000:1
Livello Rumore Audio (Modalità ECO)	29dB	29dB	29dB	29dB
Peso (Kg)	2.35	2.35	2.35	2.35
Durata Lampada ² (hrs)	7000/6500/6000/5000/10000 Eco+/Dynamic/Eco/Bright/Education cycle	7000/6500/6000/5000/10000 Eco+/Dynamic/Eco/Bright/Education cycle	7000/6500/6000/5000/10000 Eco+/Dynamic/Eco/Bright/Education cycle	6500/6000/5000 Dynamic/Eco/Bright
Dimensioni (WxDxHmm)	315 x 224 x 102	315 x 224 x 102	315 x 224 x 102	314.6 x 222.6 x 101.7
Dimensione Immagine	0.58 - 7.62m (22.9" - 300") Diagonale 4:3	0.58 - 7.62m (22.9" - 300") Diagonale 4:3	0.58 - 7.62m (22.9" - 300") Diagonale 4:3	
Rapporto di Proiezione	1.95 - 2.15:1	1.95 - 2.15:1	1.95 - 2.15:1	1.95 - 2.15:1
Tipo Di Zoom	1.1x Manuale	1.1x Manuale	1.1x Manuale	1.1x Manuale
Correzione Trapezio	± 40° Verticale	± 40° Verticale	± 40° Verticale	± 40° Verticale
Connessioni	HDMI (1.4a 3D support), VGA (YPbPr/RGB), S-Video, Composite, Audio In 3.5mm, RS232, USB Service, USB-A Power (5V-1A)	HDMI (1.4a 3D support), VGA (YPbPr/RGB), S-Video, Composite, Audio In 3.5mm, RS232, USB Service, USB-A Power (5V-1A)	HDMI (1.4a 3D support), VGA (YPbPr/RGB), S-Video, Composite, Audio In 3.5mm, RS232, USB Service, USB-A Power (5V-1A)	
Wireless Opzionale	Si	Si	Si	Si
Speaker (Watts)	2	2	2	
Borsa	No	No	No	Si
Caratteristiche				Eco+, vita fino a 10.000 ore della lampada - Ciclo Istruzione

Portatile



DS347



DS348



DX342



X316

Risoluzione	Nativa SVGA 800 x 600	Nativa SVGA 800 x 600	Nativa XGA 1024 x 768	Nativa XGA 1024 x 768
Luminosità ¹ (Modalità luminosa)	3000 ANSI Lumens	3000 ANSI Lumen	3000 ANSI Lumen	3200 ANSI Lumens
Contrasto	20,000:1	20,000:1	18,000:1	20,000:1
Livello Rumore Audio (Modalità ECO)	29dB	29dB	29dB	29dB
Peso (Kg)	2.17	2.17	2.35	2.35
Durata Lampada ² (hrs)	8000/7000/6000/5000/10000 Eco+/Dynamic/Eco/Bright/Education cycle	8000/7000/6000/5000/10000 Eco+/Dynamic/Eco/Bright/Education cycle	7000/6500/6000/5000 Eco+/Dynamic/Eco/Bright	6500/6000/5000 Dynamic/Eco/Bright
Dimensioni (WxDxHmm)	298 x 230 x 96.5	298 x 230 x 96.5	315 x 224 x 102	314.6 x 223.6 x 101.7
Dimensione Immagine			0.70 - 7.62m (22.9" - 300") Diagonale 4:3	
Rapporto di Proiezione	1.94 - 2.16:1	1.94 - 2.16:1	1.95 - 2.15:1	1.95 - 2.15:1
Tipo Di Zoom	1.1x Manuale	1.1x Manuale	1.1x Manuale	1.1x Manuale
Correzione Trapezio	± 40° Verticale	± 40° Verticale	± 40° Verticale	± 40° Vertical
Connessioni	VGA (YPbPr/RGB), Composite, USB mouse/service	2x HDMI (1.4a 3D support) + MHL, Audio out 3.5mm, USB-A Power (1A)	HDMI (1.4a 3D support), VGA (YPbPr/RGB), S-Video, Composite, Audio In 3.5mm, Audio Out 3.5mm, RS232, USB service	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), S-Video, Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB Service
Wireless Opzionale	Si	Si	Si	Si
Speaker (Watts)		2	2	2
Borsa	No	No	No	Si
Caratteristiche				Up to 10,000 hours lamp life - Education Cycle

Portatile



X340



X341



W310



W312

Risoluzione	Nativa XGA 1024 x 768	Nativa XGA 1024 x 768	Nativa WXGA 1280 x 800	Nativa WXGA 1280 x 800
Luminosità ¹ (Modalità luminosa)	3300 ANSI Lumen	3300 ANSI Lumen	3000 ANSI Lumens	3200 ANSI Lumens
Contrasto	22,000:1	22,000:1	20,000:1	20,000:1
Livello Rumore Audio (Modalità ECO)	29dB	29dB	29dB	29dB
Peso (Kg)	2.17	2.17	2.35	2.35
Durata Lampada ² (hrs)	8000/7000/6000/5000/10000 Eco+/Dynamic/Eco/Bright/Education cycle	8000/7000/6000/5000/10000 Eco+/Dynamic/Eco/Bright/Education cycle	7000/6500/6000/5000 Eco+/Dynamic/Eco/Bright	7000/6500/6000/5000 Eco+/Dynamic/Eco/Bright
Dimensioni (WxDxHmm)	298 x 230 x 96.5	298 x 230 x 96.5	315 x 224 x 102	315 x 224 x 102
Dimensione Immagine				
Rapporto di Proiezione	1.95 - 2.16:1	1.95 - 2.16:1	1.55 - 1.7:1	1.55 - 1.7:1
Tipo Di Zoom	1.1x Manuale	1.1x Manuale	1.1x Manual	1.1x Manual
Correzione Trapezio	± 40° Verticale	± 40° Verticale	± 40° Vertical	± 40° Vertical
Connessioni	HDMI (1.4a 3D support), VGA (YPbPr/RGB), Composite, Audio in 3.5mm, VGA out, Audio out 3.5mm, RS232, USB-A Power (5V-1A)	HDMI (1.4a 3D support), VGA (YPbPr/RGB), Composite, Audio in 3.5mm, VGA out, Audio out 3.5mm, RS232, USB-A Power (5V-1A)	HDMI (1.4a 3D support), VGA (YPbPr/RGB), S-Video, Composite, Audio In 3.5mm, Audio Out 3.5mm, RS232, USB service	HDMI (1.4a 3D support), VGA (YPbPr/RGB), S-Video, Composite, Audio In 3.5mm, Audio Out 3.5mm, RS232, USB service
Wireless Opzionale	Si	Si	Si	Si
Speaker (Watts)	2	2	2	2
Borsa	No	No	No	No
Caratteristiche				

Portatile



DW309



DW315



W330



W331

	DW309	DW315	W330	W331
Risoluzione	Nativa WXGA 1280 x 800	Nativa WXGA 1280 x 800	Nativa WXGA 1280 x 800	Nativa WXGA 1280 x 800
Luminosità ¹ (Modalità luminosa)	3000 ANSI Lumen	3000 ANSI Lumen	3000 ANSI Lumen	3300 ANSI Lumen
Contrasto	20,000:1	20,000:1	20,000:1	22,000:1
Livello Rumore Audio (Modalità ECO)	29dB	29dB	29dB	29dB
Peso (Kg)	2.35	2.17	2.17	2.17
Durata Lampada ² (hrs)	7000/6500/6000/5000 Eco+/Dynamic/Eco/Bright	8000/7000/6000/5000 Eco+/Dynamic/Eco/Bright	8000/7000/6000/5000 Eco+/Dynamic/Eco/Bright	8000/7000/6000/5000 Eco+/Dynamic/Eco/Bright
Dimensioni (WxDxHmm)	315 x 224 x 102	298 x 230 x 96.5	298 x 230 x 96.5	298 x 230 x 96.5
Dimensione Immagine				
Rapporto di Proiezione	1.55 – 1.7:1	1.54 – 1.7:1	1.54 – 1.7:1	1.55 – 1.73:1
Tipo Di Zoom	1.1x Manuale	1.1x Manuale	1.1x Manuale	1.1x Manuale
Correzione Trapezio	± 40° Verticale	± 40° Verticale	± 40° Verticale	± 40° Verticale
Connessioni	HDMI (1.4a 3D support), VGA (YPbPr/RGB), S-Video, Composite, Audio In 3.5mm, Audio Out 3.5mm, RS232, USB service	HDMI (1.4a 3D support), VGA (YPbPr/RGB), Composite, Audio In 3.5mm, Audio Out 3.5mm, RS232, USB service	HDMI (1.4a 3D support), VGA (YPbPr/RGB), Composite, Audio In 3.5mm, Audio Out 3.5mm, RS232, USB service	HDMI (1.4a 3D support), VGA (YPbPr/RGB), Composite, Audio In 3.5mm, Audio Out 3.5mm, RS232, USB service
Wireless Opzionale	Si	Si	Si	Si
Speaker (Watts)	2	2	2	2
Borsa	No	No	No	No
Caratteristiche				

Portatile

Desktop/Install



W316



W340



W341



W504

	W316	W340	W341	W504
Risoluzione	Nativa WXGA 1280 x 800	Nativa WXGA 1280 x 800	Nativa WXGA 1280 x 800	Nativa WXGA 1280 x 800
Luminosità ¹ (Modalità luminosa)	3400 ANSI Lumen	3400 ANSI Lumen	3600 ANSI Lumen	5000 ANSI Lumen
Contrasto	20,000:1	20,000:1	22,000:1	15,000:1
Livello Rumore Audio (Modalità ECO)	29dB	29dB	29dB	30dB
Peso (Kg)	2.35	2.17	2.17	4.6
Durata Lampada ² (hrs)	6500/6000/5000 Dynamic/Eco/Bright	8000/7000/6000/5000/10000 Eco+/Dynamic/Eco/Bright/Educationcy cle	8000/7000/6000/5000/10000 Eco+/Dynamic/Eco/Bright/Educationcy cle	5000/4500/4000/3000 Eco+/Dynamic/Eco/Bright
Dimensioni (WxDxHmm)	314.6 x 222.6 x 101.7	298 x 230 x 96.5	298 x 230 x 96.5	369 x 295 x 132
Dimensione Immagine				
Rapporto di Proiezione	1.55 – 1.7:1	1.54 – 1.7:1	1.54 – 1.7:1	1.48 - 2.35, Offset: 96.2%~112.4%
Tipo Di Zoom	1.1x Manuale	1.1x Manuale	1.1x Manuale	1.5x Manuale
Correzione Trapezio	± 40° Verticale	± 40° Verticale	± 40° Verticale	± 30° Verticale
Connessioni		2x HDMI (1.4a 3D support) + MHL, VGA (YPbPr/RGB), Composite, Audio In 3.5mm, VGA out, Audio Out 3.5mm, RS232, USB-A Power (5V-1A)	2x HDMI (1.4a 3D support) + MHL, VGA (YPbPr/RGB), Composite, Audio In 3.5mm, VGA out, Audio Out 3.5mm, RS232, USB-A Power (5V-1A)	3xHDMI (1.4a 3D support) + MHL, VGA (YPbPr/RGB), Composite, 2 x Audio In 3.5mm, VGA out, Audio Out 3.5mm, RS232, RJ45, USB-A Power (1.5A), 3D-Sync, USB mouse/service
Wireless Opzionale	Si	Si	Si	Si
Speaker (Watts)		10	10	32
Borsa	Si	No	No	No
Caratteristiche	Vita fino a 10.000 ore della lampada - Cido di Istruzione			

Desktop/Install



W505



EH504



X350



X351

	W505	EH504	X350	X351
Risoluzione	Nativa WXGA 1280 x 800	1080p 1920 x 1080	Nativa XGA 1024 x 768	Nativa XGA 1024 x 768
Luminosità ¹ (Modalità luminosa)	5200 ANSI Lumens	5000 ANSI Lumen	3400 ANSI Lumens	3600 ANSI Lumens
Contrasto	2000:1	15,000:1	18,000:1	20,000:1
Livello Rumore Audio (Modalità ECO)	37dB	30dB	29dB	29dB
Peso (Kg)	8.6 (without lens)	4.6	2.57	2.57
Durata Lampada ² (hrs)	1500 Bright	4500/4000/3500/3000 Eco+/Dynamic/Eco/Bright	7000/6500/6000/4000/8000 Eco+/Dynamic/Eco/Bright/Educationcy cle	6500/5000 Dynamic/Bright
Dimensioni (WxDxHmm)	431 x 341 x 183	369 x 295 x 132	314.6 x 223.6 x 101.7	315 x 224 x 102
Dimensione Immagine	Dipende dalla lente			
Rapporto di Proiezione	0.81 ~ 5.25 "dipende dalla lente montata"	1.41 - 2.24:1, Offset: 99%~116%	1.95 - 2.15:1	1.95 - 2.15:1
Tipo Di Zoom	Dipende dalla lente	1.6x Manuale	1.1x Manual	1.1x Manual
Correzione Trapezio	± 40° Verticale	± 30° Verticale	± 40° Vertical	± 40° Vertical
Connessioni	HDMI (1.4a 3D support), DVI-D, Display Port, 5BNC, Component Video, 2 x VGA (RGB/YPbPr), S-Video, Composite, 5 x Audio In (RCA/3.5mm), Audio Out 3.5mm, VGA Out, RJ45, RS232, USB (Remote Mouse), +12v Trigger, Wired Remote, 3D-Sync	3xHDMI (1.4a 3D support) + MHL, VGA (YPbPr/RGB), Composite, 2 x Audio In 3.5mm, VGA out, Audio Out 3.5mm, RS232, RJ45, USB-A Power (1.5A), 3D-Sync, USB mouse/service	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), S-Video, Composite, 2 x Audio In 3.5mm, Mic in (shared with Audio in 2), Audio Out 3.5mm, VGA Out, RS232, USB mouse/service, RJ45	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), S-Video, Composite, 2 x Audio In 3.5mm, Mic in (shared with Audio in 2), Audio Out 3.5mm, VGA Out, RS232, USB mouse/service, RJ45
Wireless Opzionale	Si	Si	Si	Si
Speaker (Watts)	3	32	10	10
Borsa	No	No	Si	Si
Caratteristiche	*5 x Opzioni lente [Short/STD/Long], Full Lens Shift, Crestron RoomView®, PJ-Link			

Desktop/Install



X402



X416



X600



W350

Risoluzione	Nativa XGA 1024 x 768	Nativa XGA 1024 x 768	Nativa XGA 1024 x 768	Nativa WXGA 1280 x 800
Luminosità ¹ (Modalità luminosa)	4200 ANSI Lumens	4300 ANSI Lumen	6000 ANSI Lumen	3600 ANSI Lumens
Contrasto	20,000:1	20,000:1	10,000:1	18,000:1
Livello Rumore Audio (Modalità ECO)	31dB	32dB	28dB	29dB
Peso (Kg)	2.57	2.99	3.6	2.57
Durata Lampada ² (hrs)	7000/5500/5000/3000 Eco+/Dynamic/Eco/Bright	7000/6000/5000/3000 Eco+/Dynamic/Eco/Bright	4000/3000/2500 Eco+/Dynamic/Bright	7000/6500/6000/4000/8000 Eco+/Dynamic/Eco/Bright/Educationcy cle
Dimensioni (WxDxHmm)	315 x 224 x 102	314 x 224 x 114	326 x 254 x 104	315 x 224 x 102
Dimensione Immagine			0.71 – 8.34m (28.01" – 328.38") Diagonale 4:3	
Rapporto di Proiezione	1.6 - 1.92:1	1.39 - 1.9:1	1.8 - 2.11:1	1.55 – 1.7:1
Tipo Di Zoom	1.2x Manual	1.36x Manuale	1.15x Manuale	1.1x Manual
Correzione Trapezio	± 40° Vertical	± 40° Verticale	± 40° Verticale	± 40° Vertical
Conessioni	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), S-Video, Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB mouse/service, RJ45	2 x HDMI (1.4a 3D support) + MHL v2.2, VGA (YPbPr/RGB), Composite, 2 x Audio in 3.5mm, VGA out, Audio out 3.5mm, RS232, RJ45, USB-A Power, USB mouse/service	2 x HDMI, DisplayPort, 2 x VGA (RGB/YPbPr), S-Video, Composite, 2 x Audio In (RCA/3.5mm), Audio Out 3.5mm 3.5mm, VGA Out, RJ45, RS232, USB(Remote Mouse), +12V Trigger, 3D-Sync	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), S-Video, Composite, 2 x Audio In 3.5mm, Mic in (shared with A audio in 2), Audio Out 3.5mm, VGA Out, RS232, USB mouse/service, RJ45
Wireless Opzionale	Si	Si	Si	Si
Speaker (Watts)	10	10	3	10
Borsa	Si	No	Si	Si
Caratteristiche			Facile sostituzione lampada, Crestron RoomView®, PJ-Link	

Desktop/Install



W351



W402



W415e



EH415e

Risoluzione	Nativa WXGA 1280 x 800	Nativa WXGA 1280 x 800	WXGA 1280 x 800	1080p 1920 x 1080
Luminosità ¹ (Modalità luminosa)	3800 ANSI Lumens	4500 ANSI Lumens	4500 ANSI Lumens	4200 ANSI Lumens
Contrasto	20,000:1	20,000:1	15,000:1	15,000:1
Livello Rumore Audio (Modalità ECO)	29dB	31dB	35dB	35dB
Peso (Kg)	2.57	2.57	3.4	3.4
Durata Lampada ² (hrs)	7000/6500/6000/4000/8000 Eco+/Dynamic/Eco/Bright/Educationcy cle	7000/5500/5000/3000 Eco+/Dynamic/Eco/Bright	7000/4000/3000 Eco+/Eco/Bright	7000/4000/3000 Eco+/Eco/Bright
Dimensioni (WxDxHmm)	315 x 224 x 102	315 x 224 x 102	286 x 266 x 124	286 x 266 x 124 (inc. feet)
Dimensione Immagine			0.63m – 8.05m (25" ~ 317") Diagonal 16:10	0.63 – 8.22m (25" – 324") Diagonal 16:9
Rapporto di Proiezione	1.55 – 1.7:1	1.28 - 1.536:1	1.46 - 2.2:1, Offset: 107% ~ 118%	1.39 - 2.09:1, Offset: 115% ~ 124%
Tipo Di Zoom	1.1x Manual	1.2x Manual	1.5x Manual	1.5x Manual
Correzione Trapezio	± 40° Vertical	± 40° Vertical	± 40° Vertical	± 40° Vertical
Conessioni	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), S-Video, Composite, 2 x Audio In 3.5mm, Mic in (shared with A audio in 2), Audio Out 3.5mm, VGA Out, RS232, USB mouse/service, RJ45	HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), S-Video, Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB mouse/service, RJ45	2x HDMI, 1x VGA (RGB/YPbPr), S-Video, Composite, 2 x Audio In (RCA/3.5mm), Audio Out 3.5mm, VGA Out, RJ45, RS232, USB service, 12V trigger	2x HDMI, 1x VGA (RGB/YPbPr), S-Video, Composite, 2 x Audio In (RCA/3.5mm), Audio Out 3.5mm, VGA Out, RJ45, RS232, 12V trigger, USB service
Wireless Opzionale	Si	Si	Si	Si
Speaker (Watts)	10	10	10	10
Borsa	Si	Si	Si	Si
Caratteristiche				

Desktop/Install



EH416



DH400







DU400



WU416





Risoluzione	1080p 1920 x 1080	1080p 1920 x 1080	WUXGA 1920 x 1200	WUXGA 1920 x 1200
Luminosità ¹ (Modalità luminosa)	4200 ANSI Lumen	4000 ANSI Lumen	4000 ANSI Lumen	4200 ANSI Lumen
Contrasto	20,000:1	15,000:1	15,000:1	20,000:1
Livello Rumore Audio (Modalità ECO)	32dB	32dB	32dB	32dB
Peso (Kg)	2.99	2.99	2.99	2.99
Durata Lampada ² (hrs)	7000/6000/5000/3000 Eco+/Dynamic/Eco/Bright	7000/6000/5000/3000 Eco+/Dynamic/Eco/Bright	7000/6000/5000/3000 Eco+/Dynamic/Eco/Bright	7000/6000/5000/3000 Eco+/Dynamic/Eco/Bright
Dimensioni (WxDxHmm)	314 x 224 x 114	314 x 224 x 114	314 x 224 x 114	314 x 224 x 114
Dimensione Immagine				
Rapporto di Proiezione	1.4 - 2.24:1	1.4 - 2.24:1	1.4 - 2.24:1	1.4 - 2.24:1
Tipo Di Zoom	1.6x Manual	1.6x Manuale	1.6x Manuale	1.6x Manual
Correzione Trapezio	± 40° Vertical	± 40° Vertical	± 40° Verticale	± 40° Verticale
Conessioni	2 x HDMI (1.4a 3D support) + MHL v2.2, VGA (YPbPr/RGB), Composite, 2 x Audio in 3.5mm, VGA out, Audio out 3.5mm, RS232, RJ45, USB-A Power, USB mouse/service	2 x HDMI (1.4a 3D support) + MHL v2.2, VGA (YPbPr/RGB), Composite, 2 x Audio in 3.5mm, VGA out, Audio out 3.5mm, RS232, RJ45, USB-A Power, USB mouse/service	2 x HDMI (1.4a 3D support) + MHL v2.2, VGA (YPbPr/RGB), Composite, 2 x Audio in 3.5mm, VGA out, Audio out 3.5mm, RS232, RJ45, USB-A Power, USB mouse/service	2 x HDMI (1.4a 3D support) + MHL v2.2, VGA (YPbPr/RGB), Composite, 2 x Audio in 3.5mm, VGA out, Audio out 3.5mm, RS232, RJ45, USB-A Power, USB mouse/service
Wireless Opzionale	Si	Si	Si	Si
Speaker (Watts)	10	10	10	10
Borsa	No	No	No	No
Caratteristiche				

Lente corta





	 X305ST	 X316ST	 W303ST	 W305ST
Risoluzione	Nativa XGA 1024 x 768	Nativa XGA 1024 x 768	Nativa WXGA 1280 x 800	Nativa WXGA 1280 x 800
Luminosità ¹ (Modalità luminosa)	3000 ANSI Lumen	3400 ANSI Lumens	3000 lumen	3200 ANSI Lumen
Contrasto	18,000:1	20,000:1	18,000:1	18,000:1
Livello Rumore Audio (Modalità ECO)	29dB	29dB	29dB	29dB
Peso (Kg)	2.55	2.76	2.55	2.55
Durata Lampada ² (hrs)	6000/4500 Eco/Bright	7000/6500/6000/4000/8000 Eco+/Dynamic/Eco/Bright/Educationcy cle	6000/5000/4500/10000 Eco+/Dynamic/Bright/Educationcy cle	6000/4500 Eco/Bright
Dimensioni (WxDxHmm)	288 x 220 x 86	315 x 224 x 102	288 x 220 x 86	288 x 220 x 86
Dimensione Immagine	1.00 - 5.0m (39.34" - 196.71") Diagonale 4:3			1.13 - 5.67m (44.64" - 223.21") Diagonale 16:10
Rapporto di Proiezione	0.626:1	0.617:1	0.52:1	0.52:1
Tipo Di Zoom	Fisso	1.1x Manual	Fixed	Fisso
Correzione Trapezio	± 40° Verticale	± 40° Verticale	±40° Verticale	± 40° Verticale
Connessioni	HDMI (1.4a 3D support), 2 x VGA (RGB/YpPr/Wireless), S-Video, Composite, Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB (Remote Mouse)	HDMI (1.4a 3D support), 2 x VGA (YpPr/RGB), S-Video, Composite, 2 x Audio In 3.5mm, Mic in (shared with Audio in 2), Audio Out 3.5mm, VGA Out, RS232, USB mouse/service, RJ45	HDMI (1.4a 3D support), 2 x VGA (RGB/YpPr/Wireless), S-Video, Composite, Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB remote mouse/service	HDMI (1.4a 3D support), 2 x VGA (RGB/YpPr/Wireless), S-Video, Composite, Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB (Remote Mouse)
Wireless Opzionale	Si	Si	Si	Si
Speaker (Watts)	2	10	2	2
Borsa	No	No	No	No
Caratteristiche	60" @ 0.77m, presentazioni senza ombre			60" @ 0.68m, fino a 10.000 ore di durata lampada - Education Cycle

Lente corta

Ottica ultra-corta

	 W316ST	 EH200ST	 EH415ST	 W307UST
Risoluzione	Nativa WXGA 1280 x 800	1080p 1920 x 1080	1080p 1920 x 1080	Nativa WXGA 1280 x 800
Luminosità ¹ (Modalità luminosa)	3600 ANSI Lumens	3000 ANSI Lumen	3500 ANSI Lumen	3500 ANSI Lumen
Contrasto	20,000:1	20,000:1	15,000:1	15,000:1
Livello Rumore Audio (Modalità ECO)	29dB	26dB	37dB	30dB
Peso (Kg)	2.76	2.65	3.4	7.5
Durata Lampada ² (hrs)	7000/6500/6000/4000/8000 Eco+/Dynamic/Eco/Bright/Educationcy cle	6500/6000/5000 Dynamic/Eco/Bright	7000/4000/3000 Eco+/Eco/Bright	4000/3000 Eco/Bright
Dimensioni (WxDxHmm)	315 x 224 x 102		286 x 266 x 124 (inc. feet)	357 x 367 x 231 (inc feet)
Dimensione Immagine		1.15 - 7.67m (45.3" - 300") Diagonale 16:9	59" (1.49m) ~ 152" (3.8m)	1.53 - 2.54m (60.09" - 100.02") Diagonale 16:10
Rapporto di Proiezione	0.524:1	0.49:1	0.5:1	0.35:1
Tipo Di Zoom	Fisso	Fisso	Fisso	Fisso
Correzione Trapezio	± 40° Verticale	± 40° Verticale	± 20° Verticale	± 15° Verticale
Connessioni	HDMI (1.4a 3D support), 2 x VGA (YpPr/RGB), S-Video, Composite, 2 x Audio In 3.5mm, Mic in (shared with Audio in 2), Audio Out 3.5mm, VGA Out, RS232, USB mouse/service, RJ45	2 x HDMI (1.4a 3D support) + MHL, Audio Out 3.5mm, 12V Trigger, 3D-Sync, USB Service	2x HDMI, 1x VGA (RGB/YpPr), S-Video, Composite, 2 x Audio In (RCA/3.5mm), Audio Out 3.5mm, VGA Out, RJ45, RS232, 12V trigger, USB service	HDMI (1.4a 3D support), 2 x VGA (YpPr/RGB), S-Video, Composite, 4 x Audio In (RCA/3.5mm), Audio Out 3.5mm, VGA Out, RJ45, RS232, USB (service), +12v Trigger, Microphone In
Wireless Opzionale	Si	Si	Si	Si
Speaker (Watts)	10	10	10	10
Borsa	No	Si	Si	No
Caratteristiche				60" @ 0.52m, Crestron RoomView®, PJ-Link, Shadow free presentations

Ottica ultra-corta

	 W307USTi	 X319USTir	 X319UST	 X320UST
Risoluzione	Nativa WXGA 1280 x 800	Nativa XGA 1024 x 768	Nativa XGA 1024 x 768	Nativa XGA 1024 x 768
Luminosità ¹ (Modalità luminosa)	3500 ANSI Lumen	3200 ANSI Lumen	3200 ANSI Lumen	4000 ANSI Lumen
Contrasto	15,000:1	18,000:1	18,000:1	20,000:1
Livello Rumore Audio (Modalità ECO)	30dB	26dB	26dB	28dB
Peso (Kg)	7.5	4.63	4.57	4.78
Durata Lampada ² (hrs)	4000/3000 Eco/Bright	7000/6500/6000/4500/10000 Eco+/Dynamic/Eco/Bright/Educationcy cle	7000/6500/6000/4500/10000 Eco+/Dynamic/Eco/Bright/Educationcy cle	6500/5000/5000/3000 Eco+/Dynamic/Eco/Bright
Dimensioni (WxDxHmm)	357 x 367 x 231	385 x 310 x 120	385 x 310 x 120	385 x 310 x 120
Dimensione Immagine	1.53 - 2.54m (60.09" - 100.02") Diagonale 16:10			
Rapporto di Proiezione	0.35:1	0.33:1	0.33:1	0.33:1
Tipo Di Zoom	Fisso	Fixed	Fixed	Fisso
Correzione Trapezio	± 15° Verticale	± 20° Verticale	± 20° Verticale	± 20° Verticale
Connessioni	HDMI (1.4a 3D support), 2 x VGA (YpPr/RGB), S-Video, Composite, 4 x Audio In (RCA/3.5mm), Audio Out 3.5mm, VGA Out, RJ45, RS232, USB (interactive), +12v Trigger, Microphone In	2 x HDMI (1.4a 3D support), 2 x VGA (YpPr/RGB), Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out (Shared with VGA 2), RJ45, RS232, USB remote mouse/service, 12V trigger, Mic In, 3D-Sync, USB-A Power	2 x HDMI (1.4a 3D support), 2 x VGA (YpPr/RGB), Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out (Shared with VGA 2), RJ45, RS232, USB remote mouse/service, 12V trigger, Mic In, 3D-Sync, USB-A Power	2 x HDMI (1.4a 3D support), 2 x VGA (YpPr/RGB), Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out (Shared with VGA 2), RJ45, RS232, USB remote mouse/service, 12V trigger, Mic In, 3D-Sync, USB-A Power
Wireless Opzionale	Si	Si	Si	Si
Speaker (Watts)	10	16	16	16
Borsa	No	No	No	No
Caratteristiche	60" @ 0.45m, Proiettore interattivo, Crestron RoomView®, PJ-Link, Presentazioni senza ombre			

Ottica ultra-corta

Nuovo



W319UST



W319USTir



X320USTi



W319USTi

Risoluzione	Nativa WXGA 1280 x 800	Nativa WXGA 1280 x 800	Nativa XGA 1024 x 768	Nativa WXGA 1280 x 800
Luminosità ¹ (Modalità luminosa)	3300 ANSI Lumens	3300 ANSI Lumen	4000 ANSI Lumen	3300 ANSI Lumen
Contrasto	18,000:1	18,000:1	20,000:1	18,000:1
Livello Rumore Audio (Modalità ECO)	26dB	26dB	28dB	26dB
Peso (Kg)	4.57	4.63	4.85	4.63
Durata Lampada ² (hrs)	7000/6500/6000/4500/10000 Eco+/Dynamic/Eco/Bright/Educationcy cle	7000/6500/6000/4500/10000 Eco+/Dynamic/Eco/Bright/Educationcy cle	6500/5000/5000/3000 Eco+/Dynamic/Eco/Bright	7000/6500/6000/4500/10000 Eco+/Dynamic/Eco/Bright/Educationcy cle
Dimensioni (WxDxHmm)	385 x 310 x 99	385 x 310 x 99	385 x 310 x 120	385 x 310 x 120
Dimensione Immagine				
Rapporto di Proiezione	0.27:1	0.27:1	0.33:1	0.27:1
Tipo Di Zoom	Fisso	Fixed	Fisso	Fisso
Correzione Trapezio	± 20° Vertical	± 20° Vertical	± 20° Verticale	± 20° Verticale
Connessioni	2 x HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out (Shared with VGA2), RJ45, RS232, USB remote mouse/service, 12V trigger, Mic In, USB-A Power, 3D-Sync	2 x HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out (Shared with VGA2), RJ45, RS232, USB remote mouse/service, 12V trigger, Mic In, USB-A Power, 3D-Sync	2 x HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out (Shared with VGA2), RJ45, RS232, USB remote mouse/service, 12V trigger, Mic In, 3D-Sync, USB-A Power	2 x HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out (Shared with VGA2), RJ45, RS232, USB remote mouse/service, 12V trigger, Mic In, USB-A Power, 3D-Sync
Wireless Opzionale	Si	Si	Si	Si
Speaker (Watts)	16	16	16	16
Borsa	No	No	No	No
Caratteristiche				

Ottica ultra-corta



W320UST



W320USTi



EH319UST



EH319USTi

Risoluzione	Nativa WXGA 1280 x 800	Nativa WXGA 1280 x 800	1080p 1920 x 1080	1080p 1920 x 1080
Luminosità ¹ (Modalità luminosa)	4000 ANSI Lumen	4000 ANSI Lumen	3500 ANSI Lumen	3500 ANSI Lumen
Contrasto	20,000:1	20,000:1	18,000:1	18,000:1
Livello Rumore Audio (Modalità ECO)	28dB	28dB	28dB	28dB
Peso (Kg)	4.78	4.85	4.78	4.85
Durata Lampada ² (hrs)	6500/5000/5000/3000 Eco+/Dynamic/Eco/Bright	6500/5000/5000/3000 Eco+/Dynamic/Eco/Bright	6500/5000/5000/3000 Eco+/Dynamic/Eco/Bright	3000 Bright
Dimensioni (WxDxHmm)	385 x 310 x 120	385 x 310 x 120	385 x 310 x 120	385 x 310 x 120
Dimensione Immagine				
Rapporto di Proiezione	0.27:1	0.27:1	0.25:1	0.25:1
Tipo Di Zoom	Fisso	Fisso	Fisso	Fisso
Correzione Trapezio	± 20° Verticale	± 20° Verticale	± 20° Verticale	± 20° Verticale
Connessioni	2 x HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out (Shared with VGA2), RJ45, RS232, USB remote mouse/service, 12V trigger, Mic In, USB-A Power, 3D-Sync	2 x HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out (Shared with VGA2), RJ45, RS232, USB remote mouse/service, 12V trigger, Mic In, USB-A Power, 3D-Sync	2 x HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out (condiviso con VGA2), RJ45, RS232, USB remote mouse/service, 12V trigger, Mic In, USB-A Power, 3D-Sync	2 x HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out (Shared with VGA2), RJ45, RS232, USB remote mouse/service, 12V trigger, Mic In, USB-A Power, 3D-Sync
Wireless Opzionale	Si	Si	Si	Si
Speaker (Watts)	16	16	16	16
Borsa	No	No	No	No
Caratteristiche				

Ottica ultra-corta

Alta Risoluzione



EH320UST



EH320USTi



ZH300UW



EH500

Risoluzione	1080p 1920 x 1080	1080p 1920 x 1080	Ultrawide 1920x720	1080p 1920 x 1080
Luminosità ¹ (Modalità luminosa)	4000 ANSI Lumen	4000 ANSI Lumen	3000 centre lumen (2700 ANSI)	4700 ANSI Lumen
Contrasto	20,000:1	20,000:1	10,000:1 (1800:1 full on / full off)	10,000:1
Livello Rumore Audio (Modalità ECO)	28dB	28dB	32dB	28dB
Peso (Kg)	4.8	4.85	5.5	3.6
Durata Lampada ² (hrs)	6500/5000/5000/3000 Eco+/Dynamic/Eco/Bright	6500/5000/5000/3000 Eco+/Dynamic/Eco/Bright	20000 Bright	4000/3000/2500 Eco+/Dynamic/Bright
Dimensioni (WxDxHmm)	385 x 310 x 120	385 x 310 x 120	383 x 310 x 126mm	326 x 254 x 104
Dimensione Immagine			120" to 140" (305cm to 356cm)	0.72 – 8.67m (28.41" - 341.28") Diagonal 16:9
Rapporto di Proiezione	0.25:1	0.25:1	0.25:1	1.59 - 1.91:1
Tipo Di Zoom	Fisso	Fisso	1.0x fisso	1.2x Manuale
Correzione Trapezio	± 20° Verticale	± 20° Verticale	±5° Verticale, ±5° Orizzontale	± 30° Verticale
Connessioni	2 x HDMI (V1.4a with MHL 2.0 on Input 2), 2 x VGA (YPbPr/RGB), Composite, 2 x Audio In 3.5mm jack, Audio In RCA, Microphone In, USB Type A, VGA Out (Shared with VGA Input 2), Audio Out 3.5mm jack, RJ45, RS-232, Remote Mouse / Service Port (Mini USB), Interactive 3.5mm jack,	2 x HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out (condiviso con VGA2), RJ45, RS232, USB remote mouse/service, 12V trigger, Mic In, USB-A Power, 3D-Sync	2 x HDMI (V1.4a with MHL 2.0 on Input 2), 2 x VGA (YPbPr/RGB), Composite, Audio In 3.5mm jack, Audio In RCA, Microphone In, USB Type A, VGA Out (Shared with VGA Input 2), Audio Out 3.5mm jack, RJ45, RS-232, Remote Mouse / Service Port (Mini USB), Interactive 3.5mm jack,	2 x HDMI, Display Port, 2 x VGA (RGB/YPbPr), S-Video, Composite, 2 x Audio In (RCA/3.5mm), Audio Out 3.5mm 3.5mm, VGA Out, RJ45, RS232, USB(Remote Mouse), +12V Trigger, 3D-Sync
Wireless Opzionale	Si	Si	Si	Si
Speaker (Watts)	16	16	10W	3
Borsa	No	No	No	Si
Caratteristiche			risoluzione UHD, ottica ultra-corta, luce laser-fosforo, tecnologia interattiva	Facile sostituzione lampada, Crestron RoomView®, PJ-Link

A lta Risoluzione



EH501



EH504



DH1009



DH1011i

Risoluzione	1080p 1920 x 1080	1080p 1920 x 1080	1080p 1920 x 1080	1080p 1920 x 1080
Luminosità ¹ (Modalità luminosa)	5000 ANSI Lumen	5000 ANSI Lumen	3200 ANSI Lumen	3200 ANSI Lumen
Contrasto	15,000:1	15,000:1	20,000:1	18,000:1
Livello Rumore Audio (Modalità ECO)	31dB	30dB	26dB	29dB
Peso (Kg)	4.5	4.6	2.45	2.55
Durata Lampada ² (hrs)	4000/3000/2500 Eco+/Dynamic/Bright	4500/4000/3500/3000 Eco+/Dynamic/Eco/Bright	6500/6000/5000 Dynamic/Eco/Bright	7000/6500/6000/4000 Eco+/Dynamic/Eco/Bright
Dimensioni (WxDxHmm)	386 x 280 x 162	369 x 295 x 132	315 x 224 x 114	315 x 224 x 102
Dimensione Immagine	0.76 - 7.62m (30" - 300") Diagonale 16:9		1.06 - 7.67m (41.8" - 300") Diagonale 16:9	1.06 - 7.75m (41.8" - 305") Diagonale 16:9
Rapporto di Proiezione	1.37 - 2.05:1, Offset: 115%~135%	1.41 - 2.24:1, Offset: 99%~116%	1.48 - 1.62:1	1.48 - 1.62:1
Tipo Di Zoom	1.5x Manuale	1.6x Manuale	1.1x Manuale	1.1x Manuale
Correzione Trapezio	± 40° Verticale	± 30° Verticale	± 40° Verticale	± 30° Verticale
Connessioni	HDMI, DVI-D, 2x VGA (RGB/YpPr), S-Video, Composito, 3 x Audio In (RCA/3.5mm), Mic 3.5mm, Audio Out 3.5mm, VGA Out, RJ45, RS232, 2x USB-B (Remote Mouse/Display), 2x USB-A (Reader / WiFi), +12v Trigger	3xHDMI (1.4a 3D support) + MHL, VGA (YpPr/RGB), Composito, 2 x Audio In 3.5mm, VGA out, Audio Out 3.5mm, RS232, RJ45, USB-A Power (1.5A), 3D-Sync, USB mouse/service	2 x HDMI (1.4a 3D support) + MHL, Audio Out 3.5mm, 12V Trigger, 3D-Sync, USB Service	2 x HDMI (1.4a 3D support) + MHL v1.2, VGA (YpPr), RS232, USB mouse/service, USB-A Power
Wireless Opzionale	Si	Si	Si	Si
Speaker (Watts)	16	32	10	10
Borsa	No	No	No	No
Caratteristiche	V.Lens Shift, PC-Free / presentazioni via LAN, Crestron RoomView®, PJ-Link		Pieno supporto 1080p 3D, Dynamic Black	

A lta Risoluzione



EH341



EH300



DH1017



DH400

Risoluzione	1080p 1920 x 1080	1080p 1920 x 1080	1080p 1920 x 1080	1080p 1920 x 1080
Luminosità ¹ (Modalità luminosa)	3500 ANSI Lumen	3800 ANSI Lumen	4200 ANSI Lumen	4000 ANSI Lumen
Contrasto	20,000:1	15,000:1	10,000:1	15,000:1
Livello Rumore Audio (Modalità ECO)	29dB	26dB	28dB	32dB
Peso (Kg)	2.55	3.1	3.6	2.99
Durata Lampada ² (hrs)	7000/6500/6000/4000 Eco+/Dynamic/Eco/Bright	6000/3500 Eco/Bright	4000/3000/2500 Eco+/Dynamic/Bright	7000/6000/5000/3000 Eco+/Dynamic/Eco/Bright
Dimensioni (WxDxHmm)	315 x 224 x 102	324 x 234 x 97	326 x 254 x 104	314 x 224 x 114
Dimensione Immagine	1.06 - 7.75m (41.8" - 305") Diagonal 16:9	0.77 - 9.19m (30.15" - 361.75") Diagonal 16:9	0.72 - 8.67m (28.41" - 341.28") Diagonale 16:9	
Rapporto di Proiezione	1.48 - 1.62:1	1.5 - 1.8:1	1.59 - 1.91:1	1.4 - 2.24:1
Tipo Di Zoom	1.1x Manuale	1.2x Manuale	1.2x Manuale	1.6x Manuale
Correzione Trapezio	± 30° Verticale	± 40° Verticale	± 30° Verticale	± 40° Vertical
Connessioni	2 x HDMI (1.4a 3D support) + MHL v1.2, VGA (YpPr), RS232, USB mouse/service, USB-A Power	2 x HDMI (1.4a 3D support), 2 x VGA (YpPr/RGB), Composito, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB remote mouse/service, 3D-Sync	2 x HDMI, DisplayPort, 2 x VGA (RGB/YpPr), S-Video, Composito, 2 x Audio In (RCA/3.5mm), Audio Out 3.5mm 3.5mm, VGA Out, RJ45, RS232, USB(Remote Mouse), +12V Trigger, 3D-Sync	2 x HDMI (1.4a 3D support) + MHL v2.2, VGA (YpPr/RGB), Composito, 2 x Audio in 3.5mm, VGA out, Audio out 3.5mm, RS232, RJ45, USB-A Power, USB mouse/service
Wireless Opzionale	Si	Si	Si	Si
Speaker (Watts)	10	16	3	10
Borsa	No	Si	Si	No
Caratteristiche			Facile sostituzione lampada, Crestron RoomView®, PJ-Link	

A lta Risoluzione



EH416



DU400



WU416



WU630

Risoluzione	1080p 1920 x 1080	WUXGA 1920 x 1200	WUXGA 1920 x 1200	WUXGA 1920 x 1200
Luminosità ¹ (Modalità luminosa)	4200 ANSI Lumen	4000 ANSI Lumen	4200 ANSI Lumen	6200 centre lumens (6000 ANSI)
Contrasto	20,000:1	15,000:1	20,000:1	4400:1 (1150:1 full on / full off)
Livello Rumore Audio (Modalità ECO)	32dB	32dB	32dB	35dB (Eco mode), 39dB (Bright mode)
Peso (Kg)	2.99	2.99	2.99	13.9
Durata Lampada ² (hrs)	7000/6000/5000/3000 Eco+/Dynamic/Eco/Bright	7000/6000/5000/3000 Eco+/Dynamic/Eco/Bright	7000/6000/5000/3000 Eco+/Dynamic/Eco/Bright	2000/1500 Eco/Bright
Dimensioni (WxDxHmm)	314 x 224 x 114	314 x 224 x 114	314 x 224 x 114	453 x 390 x 206mm (without protrusions)
Dimensione Immagine				50" - 300" diagonale (108 x 67cm - 646 x 404cm)
Rapporto di Proiezione	1.4 - 2.24:1	1.4 - 2.24:1	1.4 - 2.24:1	0.75 to 5.50 (dipende dalla lente)
Tipo Di Zoom	1.6x Manual	1.6x Manuale	1.6x Manual	Motorizzato
Correzione Trapezio	± 40° Vertical	± 40° Verticale	± 40° Verticale	Vertical ±20°, Horizontal ±20°
Connessioni	2 x HDMI (1.4a 3D support) + MHL v2.2, VGA (YpPr/RGB), Composito, 2 x Audio in 3.5mm, VGA out, Audio out 3.5mm, RS232, RJ45, USB-A Power, USB mouse/service	2 x HDMI (1.4a 3D support) + MHL v2.2, VGA (YpPr/RGB), Composito, 2 x Audio in 3.5mm, VGA out, Audio out 3.5mm, RS232, RJ45, USB-A Power, USB mouse/service	2 x HDMI (1.4a 3D support) + MHL v2.2, VGA (YpPr/RGB), Composito, 2 x Audio in 3.5mm, VGA out, Audio out 3.5mm, RS232, RJ45, USB-A Power, USB mouse/service	HDMI V1.3, DVI-D, VGA (YpPr), 5 BNC, Composito, VGA Out, RJ45, RS-232, 12V Trigger
Wireless Opzionale	Si	Si	Si	No
Speaker (Watts)	10	10	10	-
Borsa	No	No	No	No
Caratteristiche				5x lenti opzionali, lens shift motorizzato, operativo a 360°

Installazione

Casa



WU630



WU1500



H182X



H183X

Risoluzione	WUXGA 1920 x 1200	WUXGA 1920 x 1200	720p 1280 x 720	Nativa WXGA 1280 x 800
Luminosità ¹ (Modalità luminosa)	6200 centre lumens (6000 ANSI)	12000 centre lumen (11000 ANSI)	3200 ANSI Lumen	3200 ANSI Lumen
Contrasto	4400:1 (1150:1 full on / full off)	5000:1 (1200:1 full on / full off)	23,000:1	25,000:1
Livello Rumore Audio (Modalità ECO)	35dB (Eco mode), 39dB (Bright mode)	39dB (Bright mode) / 36dB (Eco mode)	29dB	29dB
Peso (Kg)	13.9	23.8	2.35	2.17
Durata Lampada ² (hrs)	2000/1500 Eco/Bright	2000/1500 Eco/Bright	7000/6500/6000/5000 Eco+/Dynamic/Eco/Bright	8000/7000/6000/5000 Eco+/Dynamic/Eco/Bright
Dimensioni (WxDxHmm)	453 x 390 x 206mm (without protrusions)	520 x 591 x 194mm (Senza sporgenze)	315 x 224 x 102	298 x 230 x 96.5
Dimensione Immagine	50" - 300" diagonale (108 x 67cm - 646 x 404cm)	50" - 500"		
Rapporto di Proiezione	0.75 to 5.50 (dipende dalla lente)	0.84 a 7.2 (Dipende dalla lente)	1.55 - 1.7:1	1.54 - 1.7:1
Tipo Di Zoom	Motorizzato	Motorizzato	1.1x Manuale	1.1x Manuale
Correzione Trapezio	Vertical ±20°, Horizontal ±20°	Verticale ±20°, O rizzontale ±20°	± 40° Vertical	± 40° Verticale
Connessioni	HDMI V1.3, DVI-D, VGA (YPbPr), 5 BNC, Composite, VGA Out, RJ45, RS-232, 12V Trigger	HDMI V1.4b, DVI-D, VGA (YPbPr), 5 BNC, HDBaseT, 3G-SDI, Composite, USB Wireless, VGA Out, RJ45, RS-232, Wired Remote (in/out), Service Port, 3D Sync	HDMI (1.4a 3D support), VGA (YPbPr/RGB), S-Video, Composite, Audio In 3.5mm, Audio Out 3.5mm, RS232, USB service	HDMI (1.4a 3D support), VGA (YPbPr/RGB), Composite, Audio In 3.5mm, Audio Out 3.5mm, RS232, USB service
Wireless Opzionale	No	Si	Si	Si
Speaker (Watts)	-	-	2	2
Borsa	No	No	Si	No
Caratteristiche	5x lenti opzionali, lens shift motorizzato, operativo a 360°	6x obiettivo ottico, lens shift motorizzata, due lampade, otturatore meccanico, 3G-SDI, funzionamento a 360°, proiezione ritratto, edge blending		

Casa



H112e



H114



GT760



GT1070X

Risoluzione	720p 1280 x 720	Nativa WXGA 1280 x 800	Nativa WXGA 1280 x 800	1080p 1920 x 1080
Luminosità ¹ (Modalità luminosa)	3400 ANSI Lumen	3400 ANSI Lumens	3400 ANSI Lumen	2600 ANSI Lumen
Contrasto	25,000:1	27,000:1	20,000:1	23,000:1
Livello Rumore Audio (Modalità ECO)	29dB	29dB	29dB	26dB
Peso (Kg)	2.35	2.17	2.55	2.65
Durata Lampada ² (hrs)	7000/6500/6000/5000 Eco+/Dynamic/Eco/Bright	8000/7000/6000/5000 Eco+/Dynamic/Eco/Bright	6000/4500 Eco/Bright	6500/6000/5000 Dynamic/Eco/Bright
Dimensioni (WxDxHmm)	315 x 224 x 102	298 x 230 x 96.5	288 x 220 x 86	315 x 224 x 114
Dimensione Immagine			1.13 - 5.67m (44.64" - 223.21") Diagonale 16:10	1.15 - 7.67m (45.3" - 300") Diagonal 16:9
Rapporto di Proiezione	1.55 - 1.7:1	1.54 - 1.7:1	0.52:1	0.49:1
Tipo Di Zoom	1.1x Manuale	1.1x Manuale	Fisso	Fisso
Correzione Trapezio	± 40° Verticale	± 40° Verticale	± 40° Verticale	± 40° Verticale
Connessioni	HDMI (1.4a 3D support), VGA (YPbPr/RGB), S-Video, Composite, Audio In 3.5mm, Audio Out 3.5mm, RS232, USB service	HDMI (1.4a 3D support), VGA (YPbPr/RGB), Composite, Audio In 3.5mm, Audio Out 3.5mm, RS232, USB service	HDMI (1.4a 3D support), 2 x VGA (RGB/YPbPr/Wireless), S-Video, Composite, Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB (Remote Mouse)	2 x HDMI (1.4a 3D support) + MHL, Audio Out 3.5mm, 12V Trigger, 3D-Sync, USB Service
Wireless Opzionale	Si	Si	No	Si
Speaker (Watts)	2	2	2	10
Borsa	Si	No	Si	Si
Caratteristiche			Gioco anche nella più piccola delle camere	Gaming anche nella più piccola delle camere

Casa



GT1070Xe



GT1080



GT1080e



GT5000

Risoluzione	1080p 1920 x 1080	1080p 1920 x 1080	1080p 1920 x 1080	1080p 1920 x 1080
Luminosità ¹ (Modalità luminosa)	2800 ANSI Lumen	2800 ANSI Lumen	3000 ANSI Lumen	3000 ANSI Lumen
Contrasto	23,000:1	25,000:1	25,000:1	23,000:1
Livello Rumore Audio (Modalità ECO)	26dB	26dB	26dB	28dB
Peso (Kg)	2.65	2.65	2.65	4.78
Durata Lampada ² (hrs)	6500/6000/5000 Dynamic/Eco/Bright	6500/6000/5000 Dynamic/Eco/Bright	6500/6000/5000 Dynamic/Eco/Bright	6500/5000/5000/3000 Eco+/Dynamic/Eco/Bright
Dimensioni (WxDxHmm)	315 x 224 x 114	315 x 224 x 114	315 x 224 x 114	385 x 310 x 99
Dimensione Immagine		1.15 - 7.67m (45.3" - 300") Diagonale 16:9		
Rapporto di Proiezione	0.49:1	0.49:1	0.49:1	0.25:1
Tipo Di Zoom	Fisso	Fisso	Fisso	Fisso
Correzione Trapezio	± 40° Verticale	± 40° Verticale	± 40° Verticale	± 20° Verticale
Connessioni	2 x HDMI (1.4a 3D support) + MHL v1.2, Audio Out 3.5mm, 12V trigger, 3D-Sync, USB service	2 x HDMI (1.4a 3D support) + MHL, Audio Out 3.5mm, 12V Trigger, 3D-Sync, USB Service	2 x HDMI (1.4a 3D support) + MHL v1.2, Audio Out 3.5mm, 12V trigger, 3D-Sync, USB service	2 x HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out (Shared with VGA2), RJ45, RS232, USB remote mouse/service, 12V trigger, Mic In, USB-A Power, 3D-Sync
Wireless Opzionale	Si	Si	Si	Si
Speaker (Watts)	10	10	10	16
Borsa	Si	Si	Si	No
Caratteristiche		Gaming anche nella più piccola delle camere		

Casa



GT5500



HD141X



HD421X



HD26

Risoluzione	1080p 1920 x 1080	1080p 1920 x 1080	1080p 1920 x 1080	1080p 1920 x 1080
Luminosità ¹ (Modalità luminosa)	3500 ANSI Lumen	3000 ANSI Lumen	3200 ANSI Lumen	3200 ANSI Lumen
Contrasto	25,000:1	23,000:1	25,000:1	25,000:1
Livello Rumore Audio (Modalità ECO)	28dB	26dB	26dB	26dB
Peso (Kg)	4.78	2.45	2.45	2.45
Durata Lampada ² (hrs)	6500/5000/5000/3000 Eco+/Dynamic/Eco/Bright	6500/6000/5000 Dynamic/Eco/Bright	6500 Bright	6500/6000/5000 Dynamic/Eco/Bright
Dimensioni (WxDxHmm)	385 x 310 x 99	315 x 224 x 114	315 x 224 x 114	315 x 224 x 114
Dimensione Immagine		1.06 - 7.67m (41.8" - 300") Diagonale 16:9	1.06 - 7.67m (41.8" - 300") Diagonale 16:9	1.06 - 7.67m (41.8" - 300") Diagonale 16:9
Rapporto di Proiezione	0.25:1	1.48 - 1.62:1	1.48 - 1.62:1	1.48 - 1.62:1
Tipo Di Zoom	Fisso	1.1x Manuale	1.1x Manuale	1.1x Manuale
Correzione Trapezio	± 20° Verticale	± 40° Verticale	± 40° Verticale	± 40° Verticale
Connessioni	2 x HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out (Shared with VGA 2), RJ45, RS232, USB remote mouse/service, 12V trigger, Mic In, USB-A Power, 3D-Sync	2 x HDMI (1.4a 3D support) + MHL, Audio Out 3.5mm, 12V Trigger, 3D-Sync, USB Service	2 x HDMI (1.4a 3D support) + MHL v1.2, Audio Out 3.5mm, 12V Trigger, 3D-Sync, USB Service	2 x HDMI (1.4a 3D support) + MHL, Audio Out 3.5mm, 12V Trigger, 3D-Sync, USB Service
Wireless Opzionale	Si	Si	Si	Si
Speaker (Watts)	16	10	10	10
Borsa	No	No	No	No
Caratteristiche		Full 3D 1080p Supporto, Dynamic Black	Full 3D 1080p Supporto, Dynamic Black	Full 3D 1080p Supporto, Dynamic Black

Casa



HD26LV



HD28DSE



HD151X



HD36

Risoluzione	1080p 1920 x 1080	1080p 1920 x 1080	1080p 1920 x 1080	1080p 1920 x 1080
Luminosità ¹ (Modalità luminosa)	3500 ANSI Lumen	3000 ANSI Lumen	2800 ANSI Lumen	3000 ANSI Lumen
Contrasto	25,000:1	30,000:1	28,000:1	30,000:1
Livello Rumore Audio (Modalità ECO)	29dB	28dB	27dB	27dB
Peso (Kg)	2.55	2.58	4.5	4.5
Durata Lampada ² (hrs)	7000/6500/6000/4000 Eco+/Dynamic/Eco/Bright	8000/6000/4000 Dynamic/Eco/Bright	4000/3500/2500 Dynamic/Eco/Bright	4000/3500/2500 Dynamic/Eco/Bright
Dimensioni (WxDxHmm)	315 x 224 x 102	315 x 224 x 114	386 x 280 x 162	386 x 280 x 162
Dimensione Immagine	1.06 - 7.75m (41.8" - 305") Diagonale 16:9	1.06 - 7.67m (41.8" - 300") Diagonale 16:9	0.76 - 7.67m (30" - 300") Diagonale 16:9	0.76 - 7.67m (30" - 300") Diagonale 16:9
Rapporto di Proiezione	1.48 - 1.62:1	1.48 - 1.62:1	1.37 - 2.05:1	1.37 - 2.05:1
Tipo Di Zoom	1.1x Manuale	1.1x Manuale	1.5x Manuale	1.5x Manuale
Correzione Trapezio	± 30° Verticale	± 40° Verticale ed Orizzontale	± 40° Verticale	± 40° Verticale
Connessioni	2 x HDMI (1.4a 3D support) + MHL v1.2, VGA (YPbPr), RS232, USB mouse/service, USB-A Power	2 x HDMI (1.4a 3D support) + MHL v1.2, Audio Out 3.5mm, 12V trigger, 3D-Sync, USB-A Power (0.9A), USB service	HDMI (1.4a 3D support), DVI-D, 2x VGA (RGB/YPbPr), S-Video, Composite, 3 x Audio In (RCA/3.5mm), Mic 3.5mm, Audio Out 3.5mm, VGA Out, RS232, 2x USB-B (Remote Mouse/Service), USB-A Power, +12V Trigger	HDMI (1.4a 3D support), DVI-D, 2x VGA (RGB/YPbPr), S-Video, Composite, 3 x Audio In (RCA/3.5mm), Mic 3.5mm, Audio Out 3.5mm, VGA Out, RS232, 2x USB-B (Remote Mouse/Service), USB-A Power, +12V Trigger
Wireless Opzionale	Si	Si	Si	Si
Speaker (Watts)	10	10	30	30
Borsa	No	No	No	No
Caratteristiche			V. Lens Shift	V. Lens Shift

Casa



HD161X



HD50



HD90+



HD91+

Risoluzione	1080p 1920 x 1080	1080p 1920 x 1080	1080p 1920 x 1080	1080p 1920 x 1080
Luminosità ¹ (Modalità luminosa)	2000 ANSI Lumen	2200 ANSI Lumen	1600 ANSI Lumen	1200 ANSI Lumen
Contrasto	40,000:1	50,000:1	600,000:1	600,000:1
Livello Rumore Audio (Modalità ECO)	29dB	29dB	23dB	23dB
Peso (Kg)	3.8	3.8	6.5	7
Durata Lampada ² (hrs)	7000/5000/3000 Dynamic/Eco/Bright	7000/5000/3000 Dynamic/Eco/Bright	20.000 (durata LED) Bright	20,000 (LED Life) Bright
Dimensioni (WxDxHmm)	286 x 265.5 x 124	286 x 265.5 x 124	345 x 443 x 161.5mm (inc. feet)	345 x 443 x 161.5mm (inc. feet)
Dimensione Immagine	0.76 - 7.67m (30" - 300") Diagonale 16:9	0.76 - 7.67m (30" - 300") Diagonale 16:9	0.76 - 7.67m (30" - 300") Diagonale 16:9	0.76 - 7.67m (30" - 300") Diagonale 16:9
Rapporto di Proiezione	1.39 - 2.09:1	1.39 - 2.09:1	1.22 - 1.52:1	1.5 - 2.89:1
Tipo Di Zoom	1.5x Manuale	1.5x Manuale	1.9x Manuale	1.9x Manuale
Correzione Trapezio	± 30° Verticale	± 30° Verticale	± 30° Verticale	± 30° Verticale
Connessioni	2 x HDMI (1.4a 3D support) + MHL, VGA (RGB/YPbPr), Component, Composite, 3D-Sync, 12V Trigger, RS232, USB-A Power, USB Service	2 x HDMI (1.4a 3D support) + MHL, VGA (RGB/YPbPr), Component, Composite, 3D-Sync, 12V Trigger, RS232, USB-A Power, USB Service	2 x HDMI (1.4a 3D support), VGA (RGB/YPbPr), Component, Composite, 3D-Sync, 2 x 12V trigger, RS232, USB-A Power, USB service	2 x HDMI (1.4a 3D support), VGA (RGB/YPbPr), Component, Composite, 3D-Sync, 2 x 12V trigger, RS232, USB-A Power, USB service
Wireless Opzionale	No	No	No	No
Speaker (Watts)	-	-	-	-
Borsa	No	No	No	No
Caratteristiche	PureMotion, HDMI Link, UltraDetail, Conversione 2D-3D	PureMotion, HDMI Link, UltraDetail, Conversione 2D-3D		

ProScene



EH415e



W415e



ZH300UW



WU630

Nuovo

Risoluzione	1080p 1920 x 1080	WXGA 1280 x 800	Ultrawide 1920x720	WUXGA 1920 x 1200
Luminosità ¹ (Modalità luminosa)	4200 ANSI Lumens	4500 ANSI Lumens	3000 centre lumen (2700 ANSI)	6200 centre lumens (6000 ANSI)
Contrasto	15,000:1	15,000:1	10,000:1 (1800:1 full on / full off)	4400:1 (1150:1 full on / full off)
Livello Rumore Audio (Modalità ECO)	35dB	35dB	32dB	35dB (Eco mode), 39dB (Bright mode)
Peso (Kg)	3.4	3.4	5.5	13.9
Durata Lampada ² (hrs)	7000/4000/3000 Eco+/Eco/Bright	7000/4000/3000 Eco+/Eco/Bright	20000 Bright	2000/1500 Eco/Bright
Dimensioni (WxDxHmm)	286 x 266 x 124 (inc. feet)	286 x 266 x 124	383 x 310 x 126mm	453 x 390 x 206mm (without protrusions)
Dimensione Immagine	0.63 – 8.22m (25" – 324") Diagonal 16:9	0.63m – 8.05m (25" ~ 317") Diagonal 16:10	120" to 140" (305cm to 356cm)	50" - 300" diagonale (108 x 67cm - 646 x 404cm)
Rapporto di Proiezione	1.39 - 2.09:1, Offset: 115%~124%	1.46 - 2.2:1, Offset: 107% ~ 118%	0.25:1	0.75 to 5.50 (dipende dalla lente)
Tipo Di Zoom	1.5x Manual	1.5x Manual	1.0x fisso	Motorizzato
Correzione Trapezio	± 40° Vertical	± 40° Vertical	±5° Verticale, ±5° Orizzontale	Vertical ±20°, Horizontal ±20°
Conessioni	2x HDMI, 1x VGA (RGB/YPbPr), S-Video, Composite, 2 x Audio In (RCA/3.5mm), Audio Out 3.5mm, VGA Out, RJ45, RS232, 12V trigger, USB service	2x HDMI, 1x VGA (RGB/YPbPr), S-Video, Composite, 2 x Audio In (RCA/3.5mm), Audio Out 3.5mm, VGA Out, RJ45, RS232, USB service, 12V trigger	2 x HDMI (V 1.4a with MHL 2.0 on Input 2), 2 x VGA (YPbPr / RGB), Composite, Audio In 3.5mm jack, Audio In RCA, Microphone In, USB Type A, VGA Out (Shared with VGA Input 2), Audio Out 3.5mm jack, RJ45, RS-232, Remote Mouse / Service Port (Mini USB), Interactive 3.5mm jack,	HDMI V1.3, DVI-D, VGA (YPbPr), 5 BNC, Composite, VGA Out, RJ45, RS-232, 12V Trigger
Wireless Opzionale	Si	Si	Si	No
Speaker (Watts)	10	10	10W	-
Borsa	Si	Si	No	No
Caratteristiche			risoluzione UHD, ottica ultra-corta , luce laser-fosforo, tecnologia interattiva	5x lenti opzionali, lens shift motorizzato, operativo a 360°

ProScene



EH500



X501



W504



EH501

Risoluzione	1080p 1920 x 1080	Nativa XGA 1024 x 768	Nativa WXGA 1280 x 800	1080p 1920 x 1080
Luminosità ¹ (Modalità luminosa)	4700 ANSI Lumen	4500 ANSI Lumen	5000 ANSI Lumen	5000 ANSI Lumen
Contrasto	10,000:1	15,000:1	15,000:1	15,000:1
Livello Rumore Audio (Modalità ECO)	28dB	27dB	30dB	31dB
Peso (Kg)	3.6	4.5	4.6	4.5
Durata Lampada ² (hrs)	4000/3000/2500 Eco+/Dynamic/Bright	4000/3000/2500 Eco+/Dynamic/Bright	5000/4500/4000/3000 Eco+/Dynamic/Eco/Bright	4000/3000/2500 Eco+/Dynamic/Bright
Dimensioni (WxDxHmm)	326 x 254 x 104	386 x 280 x 162	369 x 295 x 132	386 x 280 x 162
Dimensione Immagine	0.72 – 8.67m (28.41" – 341.28") Diagonal 16:9	0.76 – 7.62m (30" – 300") Diagonale 4:3		0.76 – 7.62m (30" – 300") Diagonale 16:9
Rapporto di Proiezione	1.59 - 1.91:1	1.39 - 2.26:1, Offset: 115%	1.48 - 2.35, Offset: 96.2%~112.4%	1.37 - 2.05:1, Offset: 115%~135%
Tipo Di Zoom	1.2x Manuale	1.6x Manuale	1.5x Manuale	1.5x Manuale
Correzione Trapezio	± 30° Verticale	± 40° Verticale	± 30° Vertical	± 40° Verticale
Conessioni	2 x HDMI, Display Port, 2 x VGA (RGB/YPbPr), S-Video, Composite, 2 x Audio In (RCA/3.5mm), Audio Out 3.5mm 3.5mm, VGA Out, RJ45, RS232, USB(Remote Mouse), +12V Trigger, 3D-Sync	HDMI, DVI-D, 2x VGA (RGB/YPbPr), S-Video, Composite, 3 x Audio In (RCA/3.5mm), Mic 3.5mm, Audio Out 3.5mm, VGA Out, RJ45, RS232, 2x USB-B (Remote Mouse/Display), 2x USB-A (Reader / WiFi), +12V Trigger	3xHDMI (1.4a 3D support) + MHL, VGA (YPbPr/RGB), Composite, 2 x Audio In 3.5mm, VGA out, Audio Out 3.5mm, RS232, RJ45, USB-A Power (1.5A), 3D-Sync, USB mouse/service	HDMI, DVI-D, 2x VGA (RGB/YPbPr), S-Video, Composite, 3 x Audio In (RCA/3.5mm), Mic 3.5mm, Audio Out 3.5mm, VGA Out, RJ45, RS232, 2x USB-B (Remote Mouse/Display), 2x USB-A (Reader / WiFi), +12V Trigger
Wireless Opzionale	Si	Si	Si	Si
Speaker (Watts)	3	30	32	16
Borsa	Si	No	No	No
Caratteristiche	Facile sostituzione lampada, Crestron RoomView®, PJ-Link	V.Lens Shift, PC-Free / LAN presentation, Crestron RoomView®, PJ-Link		V.Lens Shift, PC-Free / presentazioni via LAN, Crestron RoomView®, PJ-Link

ProScene



EH504



X515



W515



W515T

Risoluzione	1080p 1920 x 1080	Nativa XGA 1024 x 768	Nativa WXGA 1280 x 800	Nativa WXGA 1280 x 800
Luminosità ¹ (Modalità luminosa)	5000 ANSI Lumen	6500 ANSI Lumen	6000 ANSI Lumen	6000 ANSI Lumen
Contrasto	15,000:1	10,000:1	10,000:1	10,000:1
Livello Rumore Audio (Modalità ECO)	30dB	28	28	28
Peso (Kg)	4.6	5.9	5.9	5.9
Durata Lampada ² (hrs)	4500/4000/3500/3000 Eco+/Dynamic/Eco/Bright	5000/3000 Eco/Bright	5000/2500 Eco/Bright	5000/2500 Eco/Bright
Dimensioni (WxDxHmm)	369 x 295 x 132	424 x 344 x 160	424 x 344 x 160	424 x 344 x 160
Dimensione Immagine				
Rapporto di Proiezione	1.41 - 2.24:1, Offset: 99%~116%	1.243~2.238:1, Offset: 95%~105%	1.26~2.268:1, Offset: 105%~125%	1.26~2.268:1, Offset: 105%~125%
Tipo Di Zoom	1.6x Manuale	1.8x Manuale	1.8x Manuale	1.8x Manuale
Correzione Trapezio	± 30° Verticale	± 30° Vertical ± 30° Horizontal	± 30° Verticale ± 30° Orizzontale	± 30° Verticale ± 30° Orizzontale
Conessioni	3xHDMI (1.4a 3D support) + MHL, VGA (YPbPr/RGB), Composite, 2 x Audio In 3.5mm, VGA out, Audio Out 3.5mm, RS232, RJ45, USB-A Power (1.5A), 3D-Sync, USB mouse/service	2 x HDMI (1.4a 3D support) + MHL, Display Port, 2 x VGA (YPbPr/RGB), S-Video, Composite, 3 x Audio In (RCA/3.5mm), Mic In, Audio Out 3.5mm, VGA Out, RS232, USB-A Power (1.5A), USB mouse/service, RJ45, 12V trigger, 3D-Sync, Wired remote	2 x HDMI (1.4a 3D support) + MHL, Display Port, 2 x VGA (YPbPr/RGB), S-Video, Composite, 3 x Audio In (RCA/3.5mm), Mic In, Audio Out 3.5mm, VGA Out, RS232, USB-A Power (1.5A), USB mouse/service, RJ45, 12V trigger, 3D-Sync, Wired remote	1 x HDBaseT(RJ-45) 2 x HDMI (1.4a 3D support) + MHL, Display Port, 2 x VGA (YPbPr/RGB), S-Video, Composite, 3 x Audio In (RCA/3.5mm), Mic In, Audio Out 3.5mm, VGA Out, RS232, USB-A Power (1.5A), USB mouse/service, RJ45, 12V trigger, 3D-Sync, Wired remote
Wireless Opzionale	Si	Si	No	No
Speaker (Watts)	32	20	20	20
Borsa	No	No	No	No
Caratteristiche		V/H Lens Shift, PC-Free / LAN presentation, Crestron RoomView®, PJ-Link	V/H Lens Shift, PC-Free / LAN presentation, Crestron RoomView®, PJ-Link	V/H Lens Shift, PC-Free / LAN presentation, Crestron RoomView®, PJ-Link

ProScene



EH515



EH515T



WU515



WU515T

Risoluzione	1080p 1920 x 1080	1080p 1920 x 1080	WUXGA 1920 x 1200	WUXGA 1920 x 1200
Luminosità ¹ (Modalità luminosa)	5500 ANSI Lumen	5500 ANSI Lumen	6000 ANSI Lumen	6000 ANSI Lumen
Contrasto	10,000:1	10,000:1	10,000:1	10,000:1
Livello Rumore Audio (Modalità ECO)	28	28	28	28
Peso (Kg)	5.9	5.9	5.9	5.9
Durata Lampada ² (hrs)	4000/3000 Eco/Bright	5000/3000 Eco/Bright	5000/3000 Eco/Bright	5000/3000 Eco/Bright
Dimensioni (WxDxHmm)	424 x 344 x 160	424 x 344 x 160	424 x 344 x 160	424 x 344 x 160
Dimensione Immagine				
Rapporto di Proiezione	1.2:1 ~2.160:1	1.2~2.160:1, Offset: 105%~130%	1.2~2.160:1, Offset: 100%~120%	1.2~2.160:1, Offset: 100%~120%
Tipo Di Zoom	1.8x Manuale	1.8x Manuale	1.8x Manuale	1.8x Manuale
Correzione Trapezio	± 30° Verticale ± 30° Orizzontale	± 30° Verticale ± 30° Orizzontale	± 30° Vertical ± 30° Orizzontale	± 30° Vertical ± 30° Horizontal
Connessioni	2 x HDMI (1.4a 3D support) + MHL, Display Port, 2 x VGA (YPbPr/RGB), S-Video, Composite, 3 x Audio In (RCA/3.5mm), Mic In, Audio Out 3.5mm, VGA Out, RS232, USB-A Power (1.5A), USB mouse/service, RJ45, 12V trigger, 3D-Sync, Wired remote	1 x HDBaseT (RJ-45) 2 x HDMI (1.4a 3D support) + MHL, Display Port, 2 x VGA (YPbPr/RGB), S-Video, Composite, 3 x Audio In (RCA/3.5mm), Mic In, Audio Out 3.5mm, VGA Out, RS232, USB-A Power (1.5A), USB mouse/service, RJ45, 12V trigger, 3D-Sync, Wired remote	2 x HDMI (1.4a 3D support) + MHL, Display Port, 2 x VGA (YPbPr/RGB), S-Video, Composite, 3 x Audio In (RCA/3.5mm), Mic In, Audio Out 3.5mm, VGA Out, RS232, USB-A Power (1.5A), USB mouse/service, RJ45, 12V trigger, 3D-Sync, Wired remote	1 x HDBaseT (RJ-45) 2 x HDMI (1.4a 3D support) + MHL, Display Port, 2 x VGA (YPbPr/RGB), S-Video, Composite, 3 x Audio In (RCA/3.5mm), Mic In, Audio Out 3.5mm, VGA Out, RS232, USB-A Power (1.5A), USB mouse/service, RJ45, 12V trigger, 3D-Sync, Wired remote
Wireless Opzionale	Si	Si	Si	Si
Speaker (Watts)	20	20	20	20
Borsa	No	No	No	No
Caratteristiche	V/H Lens Shift, PC-Free / LAN presentation, Crestron RoomView®, PJ-Link	V/H Lens Shift, PC-Free / LAN presentation, Crestron RoomView®, PJ-Link	V/H Lens Shift, PC-Free / LAN presentation, Crestron RoomView®, PJ-Link	V/H Lens Shift, PC-Free / LAN presentation, Crestron RoomView®, PJ-Link

ProScene



X605



W505



EH503



EH505

Risoluzione	Nativa XGA 1024 x 768	Nativa WXGA 1280 x 800	1080p 1920 x 1080	WUXGA 1920 x 1200
Luminosità ¹ (Modalità luminosa)	6000 ANSI Lumens	5200 ANSI Lumens	5200 ANSI Lumen	5000 ANSI Lumen
Contrasto	2000:1	2000:1	2000:1	2000:1
Livello Rumore Audio (Modalità ECO)	37dB	37dB	37dB	37dB
Peso (Kg)	8.6 (without lens)	8.6 (without lens)	8.6 (senza lenti)	8.6 (senza lente)
Durata Lampada ² (hrs)	3500 Bright	1500 Bright	3500/1500 Eco/Bright	3500/1500 Eco/Bright
Dimensioni (WxDxHmm)	431 x 341 x 183	431 x 341 x 183	431 x 341 x 183	431 x 341 x 183
Dimensione Immagine	Dependent upon lens	Dipende dalla lente	Dipende dalla lente	Dipende dalla lente
Rapporto di Proiezione	0.8 ~ 5.18 "lens dependent"	0.81 ~ 5.25 "dipende dalla lente montata"	"Dipendente Lente" 0.77 ~ 5.00	0.77 ~ 2.89 "dipende dalla lente montata"
Tipo Di Zoom	Dependent upon lens	Dipende dalla lente	Dipende dalla lente	Dipende dalla lente
Correzione Trapezio	± 30° Vertical	± 40° Verticale	± 40° Verticale	± 40° Verticale
Connessioni	HDMI (1.4a 3D support), DVI-D, Display Port, 5BNC, Component Video, 2 x VGA (RGB/YPbPr), S-Video, Composite, 5 x Audio In (RCA/3.5mm), Audio Out 3.5mm, VGA Out, RJ45, RS232, USB (Remote Mouse), +12v Trigger, Wired Remote, 3D-Sync	HDMI (1.4a 3D support), DVI-D, Display Port, 5BNC, Component Video, 2 x VGA (RGB/YPbPr), S-Video, Composite, 5 x Audio In (RCA/3.5mm), Audio Out 3.5mm, VGA Out, RJ45, RS232, USB (Remote Mouse), +12v Trigger, Wired Remote, 3D-Sync	HDMI (1.4a 3D support), DVI-D, Display Port, 5BNC, Component Video, 2 x VGA (RGB/YPbPr), S-Video, Composite, 5 x Audio In (RCA/3.5mm), Audio Out 3.5mm, VGA Out, RJ45, RS232, USB (Remote Mouse), +12v Trigger, Wired Remote, 3D-Sync	HDMI (1.4a 3D support), DVI-D, Display Port, 5BNC, Component Video, 2 x VGA (RGB/YPbPr), S-Video, Composite, 5 x Audio In (RCA/3.5mm), Audio Out 3.5mm, VGA Out, RJ45, RS232, USB (Remote Mouse), +12v Trigger, Wired Remote
Wireless Opzionale	Si	Si	Si	Si
Speaker (Watts)	3	3	3	3
Borsa	No	No	No	No
Caratteristiche	"5 x Optional Lens [Short/STD/Long], Full Lens Shift, Crestron RoomView®, PJ-Link	"5 x Opzioni lente [Short/STD/Long], Full Lens Shift, Crestron RoomView®, PJ-Link	"5 x lenti [Breve / semi breve / STD / Lungo / molto lungo], full lens shift, Crestron RoomView®, PJ-Link	"5 x Lenti Opzionali [Short/STD/Long], Full Lens Shift, Crestron RoomView®, PJ-Link

ProScene



ZU650



EH7700



WU1500



15000L Advanced Stacking

Risoluzione	WUXGA 1920 x 1200	WUXGA 1920 x 1200	WUXGA 1920 x 1200	WUXGA 1920 x 1200
Luminosità ¹ (Modalità luminosa)	6000 centre lens (5,500 ANSI lumen)	7000 Centre Lumens usando Bright colour wheel (di serie e Dual Lamp) 6500 ANSI Lumens	12000 centre lumen (11000 ANSI)	15000 lumen utilizzando impostazioni della modalità "brillante"
Contrasto	2,000,000:1 ExtremeBlack enabled (2000:1 full on/off)	5000:1	5000:1 (1200:1 full on / full off)	2500:1
Livello Rumore Audio (Modalità ECO)	33dB	39dB	39dB (Bright mode) / 36dB (Eco mode)	
Peso (Kg)	18Kg	24Kg (senza lente)	23.8	
Durata Lampada ² (hrs)	20000 Bright	2000 Eco	2000/1500 Eco/Bright	2500/2000 Bright
Dimensioni (WxDxHmm)	484 x 509 x 185mm senza lente	439 x 549 x 235mm	520 x 591 x 194mm (Senza sporgenze)	
Dimensione Immagine	Dipende dalla lente		50" - 500"	Dipende dalla lente
Rapporto di Proiezione	0.75 ~ 5.50 "lens dependent"	0.77 ~ 6.98 "dipende dalla lente utilizzata"	0.84 a 7.2 (Dipende dalla lente)	
Tipo Di Zoom	Motorised		Motorizzato	Dipende dalla lente
Correzione Trapezio		Verticale ±20°	Verticale ±20°, Orizzontale ±20°	
Connessioni	1 x HDMI, 1 x DVI-D, HDBaseT, Component Video, 1 x VGA, VGA Out, RJ45, RS232, wired remote in, wired remote out, USB A		HDMI V1.4b, DVI-D, VGA (YPbPr), 5 BNC, HDBaseT, 3G-SDI, Composite, USB Wireless, VGA Out, RJ45, RS-232, Wired Remote (in/out), Service Port, 3D Sync	HDMI, DVI-D, VGA Out, HDMI Out, RJ45
Wireless Opzionale	Si	No	Si	No
Speaker (Watts)	-		-	
Borsa	No	No	No	No
Caratteristiche	5 x optional Lens, motorised full lens shift, Crestron RoomView®, PJ-Link, 360° operation		6x obiettivo ottico, lens shift motorizzata, due lampade, otturatore meccanico, 3G-SDI, funzionamento a 360°, proiezione ritratto, edge blending	5 x lenti opzionali, spostamento motorizzato Lente completo, Crestron RoomView®, PJ-Link, disponibile in bianco, Funzionamento 360°

ProScene



HQView 320



HQView 325



HQView 530



GB-200

	HQView 320	HQView 325	HQView 530	GB-200
Risoluzione	1080p 1920 x 1080	1080p 1920 x 1080	1080p 1920 x 1080	1080p 1920 x 1080
Luminosità ¹ (Modalità luminosa)	0 lumens			
Contrasto				
Livello Rumore Audio (Modalità ECO)				
Peso (Kg)	1kg			
Durata Lampada ² (hrs)				
Dimensioni (WxDxHmm)				
Dimensione Immagine				
Rapporto di Proiezione				
Tipo Di Zoom				
Correzione Trapezio				
Connessioni				
Wireless Opzionale		No	No	No
Speaker (Watts)				
Borsa		No	No	No
Caratteristiche				



Optoma Europe Limited
42 Caxton Way, Watford Business Park,
Watford, Hertfordshire. WD18 8QZ
Tel: +44 (0) 1923 691800
Fax: +44 (0) 1923 691888

www.optomaeurope.com



† "Contrasto ANSI" è una tecnica di misura per il contrasto riconosciuta come descritto nella norma IEC 61947-1

Copyright © 2013, Optoma Europe Ltd. ThemeScene ® è un marchio registrato di Optoma Europe Ltd. DLP ®, BrilliantColor™ e il logo DLP sono marchi registrati di Texas Instruments.

 è un marchio di SRS Labs, Inc. La tecnologia WOW è registrata su licenza di SRS Labs, Inc.

Crestron®, Crestron e il marchio RoomView® sono marchi registrati di Crestron Electronics, Inc. Tutti gli altri nomi di prodotti e nomi di aziende sono utilizzati solo a scopo identificativo e possono essere marchi o marchi registrati dei rispettivi proprietari. * Tipica durata della lampada tramite test. Può variare in dipendenza dell'uso o delle condizioni ambientali. Tutte le immagini dei prodotti sono a fini descrittivi. Mentre ogni cura è presa per fornire immagini accurate dei nostri prodotti, i prodotti reali possono differire leggermente. Alcune immagini dei prodotti possono essere state alterate digitalmente per aggiungere un logo Optoma al pannello frontale. Optoma si riserva il diritto di modificare o alterare le immagini reali del prodotto o dei prodotti senza preavviso. Salvo errori ed omissioni, tutte le specifiche sono soggette a modifiche senza preavviso. Alcune immagini possono essere simulate.